

# Hardwaxoil Magic

## PRODUCT DESCRIPTION

Flooring oil suitable for oil finishing of wooden floors. Good filling properties, natural colour, good chemical and mechanical resistance. Does not shine and is very matt. The durability can be improved by adding the hardener UA 5% (optional).

## TECHNICAL DATA

Viscosity	+/- 35-45 sec. (Din 4mm/20°C)
SOLID CONTENTS	+/- 51% by weight
DENSITY	+/- 0,91 kg/lit.
GLOSS	<b>matt</b>

## COLOURS

**Standard:** natural, natural white, white, extra white, grey, old grey, smoked oak, black.

CONFORM THE EUROPEAN DECO-PAINT DIRECTIVE 2010



5L 1L

## PREPARATION

Sand the surface with grain 100 – 120 and afterwards remove sanding dust.

## USER TIPS

Before use, shake and stir well. Can be applied by paintbrush, polishing machine, roller or cloth. After applying the oil, the excess oil has to be wiped, brushed and or polished into the wood. 2 coats are recommended for hard wood. For soft wood 3 coats are recommended. For industrial use, please contact our service centre.



## DRYING TIMES

Can be overcoated after 6 hours.

The drying time is strongly depending on the applied quantity, the temperature and the ventilation of the room. Through a higher temperature and a good ventilation, drying time is reduced.

## APPLYING QUANTITY

30 to 35 m<sup>2</sup> per liter

## AFTER TREATMENT

Clean regularly with flooringsoap Ciranova. Depending on the use of the floor, use maintenance oil 1 time a year. For thorough cleaning, use Intensive Cleaner Ciranova®.

## PRODUCT INFORMATION

Shelf life: up to 2 year in a well closed original packaging.

## SPECIAL QUALITIES

Used cloths or pads should be plunged in water because of the danger of spontaneous combustion.

We recommend Hardwaxoil Magic Natural as topcoat on the pigmented Hardwaxoils.

Hardwaxoil Magic Natural and Natural White can be used as a primer to isolate the water borne stain, so it can be overcoated with a lacquer.

As with all wood finishing always do a test area first to safeguard against an undesirable outcome. This technical data sheet is merely a guide and not a guarantee. All products are formulated to the best of our knowledge. The information is given as a result of many years experience. This product has had extensive tests carried out.

## Produced by Debal Coatings nv

Industrieweg 29 - 8800 Beveren-  
Roeselare Belgium tel. +32 (0) 51 30 11 40  
fax +32 (0) 51 31 26 48  
ciranova@ciranova.be